## **PAYMENT TERMINAL C20**

## **SPECIFICATIONS**

| PHYSICAL CHARA                                   | ACTERISTICS  |
|--|--|
| Dimensions                                       | 166,7 <sup>L</sup> x 82,1 <sup>B</sup> x 25 <sup>H</sup> mm  |
| Weight   | ~450g  |
| Display  | 3.5" color TFT with adaptive brightness  |
| Touch  | Capacitive   |
| PIN  | 4x4 ADA-compliant layout and reflective characters   |
| Notification                                     | Audio: Mono speaker & 3.5 audio jack for voice guidance  |
| Card guide                                       | LED chip card light guide for improved user guidance.  |
| PERFORMANCE                                      |  |
| CPU  | 2,0 GHz Cortex A53 Quad Core Processor   |
| Capacity   | 64GB eMMC internal storage<br>4GB SDRAM  |
| os   | Android 12   |
| CARD READERS                                     |  |
| Magnetic stripe                                  | ISO 7811 compliant with 3 tracks (1,2,3)   |
| Smart card                                       | ISO7816-1/2/3 <sup>(1,8)(,3)(,5)()</sup> . Synchronous and asynchronous card protocol. EMV approved  |
| Contactless                                      | ISO18092 NFC, ISO14443 type A/B, MiFare  |
| Supports the following* contactless applications | MasterCard PayPass, M/Chip, PayPass MagStripe, Visa pay-<br>Wave MSD, VISA payWave, qVSDC, Discovery Zip, American<br>Express ExpressPay, JCB J-Speedy, UnionPay |
| SAM/SIM  | 2x SAM, 1x SD Card   |
| PRINTER  |  |
| Speed  | 15-20 lines per second   |
| Paper  | 48mm paper width with 40mm print width   |
| COMMUNICATION                                    |  |
| Wi-Fi  | 802.11 a/b/g/n/ac (2,4 & 5GHz)   |
| Bluetooth  | 5.0 Dual mode  |
| Interface  | USB or RS232 + PoE   |
| OTHER  |  |
| IP Rating  | 53   |
|  | This means that the product can withstand light rain, spilled drinks and dusty environments <sup>1</sup>   |
| USER ENVIRONM                                    | ENT  |
| Operating temp.                                  | 0°C to 50°C  |
|  | -20°C to 60°C  |
| Storage temp.                                    | -20 C to 60 C  |

| <sup>1</sup> The IP rating is provided for reference only and does not constitute a guarantee |  |  |
|---|--|--|
| of performance under all conditions. Specific conditions and limitations apply.               |  |  |
| Please refer to the official IP classification standards for exact requirements and           |  |  |
| test specifications.  |  |  |

| CERTIFICATIONS  |         |  |
|---|---------|--|
| PCI PTS   | 6.x     |  |
| EMV   | L1 & L2 |  |
| EVM CTLS  | L1      |  |
| ACCESSORIES AND PERIPHERALS   |         |  |
| C20 can be fitted with a range of accessories including terminal pole mount and desk stand.   |         |  |
| WARRANTY AND CONDITIONS   |         |  |
| With reservation for Westpay's general terms and conditions, C20 can be complemented with standard service solutions, including a swap warranty that will deliver a replacement unit directly to the store. |         |  |



